



PLAN




ELEVATION

- GENERAL NOTES:
- ALL MORTAR JOINTS ARE 1/2" ± 1/8".
 - BOND BRICKWORK WITH FULL HEADERS EVERY THREE COURSES.
 - CONCAVE TOOL ALL EXPOSED JOINTS.
 - CONSTRUCT THE BASE WITH FORMS.
 - USE CLASS 'B' CONCRETE.
 - PAY FOR CONCRETE AS BRICK MASONRY.
 - CONCRETE BRICK MAY BE USED IN LIEU OF CLAY BRICK.
 - JUMBO BRICK WILL BE PERMITTED.



END ELEVATION



TYPICAL SECTION THRU WALL

DIMENSIONS AND QUANTITIES								
COMMON DIMENSIONS							QUANTITIES	
SPAN	RISE	THICK	H	B	G	M	BRICK YD ³	CONC. YD ³
40"	31"	0.109	3'-7"	2'-0"	5'-8"	1'-11"	1.525	0.715
46"	36"	0.109	4'-0"	2'-4"	6'-5"	2'-2"	2.025	0.930
53"	41"	0.109	4'-5"	2'-8"	7'-2"	2'-6"	2.626	1.180
60"	46"	0.109	4'-10"	2'-8"	8'-0"	2'-9"	3.332	1.269
66"	51"	0.109	5'-4"	3'-0"	8'-10"	3'-0"	4.074	1.560

* QUANTITIES BASED OF 2'-0"